

3/7/1

DIALOG(R) File 347:JAPIO
(c) 2001 JPO & JAPIO. All rts. reserv.

05560320 **Image available**

PNEUMATIC RADIAL TIRE

PUB. NO.: 09-175120 JP 9175120 A]
PUBLISHED: July 08, 1997 (19970708)
INVENTOR(s): TOMITA ARATA
APPLICANT(s): BRIDGESTONE CORP [000527] (A Japanese Company or Corporation)
 , JP (Japan)
APPL. NO.: 07-342110 [JP 95342110]
FILED: December 28, 1995 (19951228)

ABSTRACT

PROBLEM TO BE SOLVED: To markedly extend a rejection limit of a tire by effectively suppressing uneven wearing of a tread shoulder part.

SOLUTION: This tire has a bead core, carcass ply comprising a radial chord layer, belt comprising one or more chord layers and a tread. In both side parts of the tread, a peripheral direction main groove 5 extended in the peripheral direction and many cross direction grooves 6, extended in the tire axial direction between the peripheral direction main groove and a tread end part to open one end part to the peripheral direction main groove and the other end part to a tread end, are provided, an uneven wearing preventing block 7, having a tire axial direction width 50% or more the length of the cross direction groove 6, is provided therein, the tire is rim-assembled in a standard rim by a regular internal pressure, when a regular load is statically loaded, the uneven wearing preventing block 7 is grounded further prevented from coming into contact with a groove side wall of the cross direction groove 6.